



Declaration of Performance

Number: L/VC2/001

1. Unique identification code of the product-type:

Novia VC2

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Flexible sheets for waterproofing – Plastic and rubber vapour control layers (according to EN 13984:2013)

3. Name and contact address of the manufacturer:

Novia Ltd
Unit 12 Heronden Road
Park Wood Industrial Estate
Maidstone
Kent
ME15 9YR

4. Name of the authorized representative whose mandate covers the tasks specified in Article 12, Paragraph 2:

Adrian Chisholm

5. System of assessment and verification of constancy of performance of the construction product:

System 3

6. Notified body:

Technicky A Skusobny Ustav Stavebny n.o. Notified Body 1301 performed the initial type test according to EN 13984:2013


7. Declared Performance:

Essential Characteristics	Specified value	Bottom tolerance	Top tolerance	Unit	Test standard
Length	50	50	51	m	EN1848-2
Width	1500	1493	1523	mm	EN1848-2
Mass per unit area (weight)	116	104.5	131.9	g/m ²	EN1849-2
Tensile strength (MD)	345	250	395	N/50mm	EN12311-1
Tensile strength (CD)	320	250	390	N/50mm	EN12311-1
Max elongation at tensile strength (MD)	27	15	40	%	EN12311-1
Max elongation at tensile strength (CD)	21	10	40	%	EN12311-1

Novia®

Nail tear resistance (MD)	215	180	350	N	EN12310-1
Nail tear resistance (CD)	195	150	280	N	EN12310-1
Water vapour transmission properties	12	6	16	g/m ² *day	EN1931/ EN12572
Water vapour transmission properties after ageing	Pass				EN1931/ EN12572
Water vapour transmission properties sd	3	2	6	m	EN1931/ EN12572
Reaction to fire	E			Class	EN13501-1
Reaction to water penetration	W1			Class	EN1928:2000/ EN13111

8. The performance of the product according to point no.1 corresponds to the declared performances under section 7.



.....
Adrian Chisholm, Managing Director
Novia Ltd

.....11.01.2016....
Date