



# Material Specification Sheet

**Product Code** 85PEGW

**Product Details** Gloss white Polyethylene film with Top Coating.  
Printable with Letterpress, Screenprinting, Hot Stamping and Thermal Transfer.

## Face Material

**Description** Polyethylene film  
**Finish and Colour** Gloss White  
**Weight / Thickness** 85 micron / 83 gsm

## Adhesive

**Type** Permanent, Acrylic  
**Minimum Application Temp** -5 °C  
**In Service Temp** -40 °C to +120 °C  
**Initial Tack** High  
**Ultimate Adhesion** High  
**Notes** High clarity and cohesion with strong adhesion to apolar substrates.  
Approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the Germal Recommendations XIV and complies with FDA 175.105.

## Release Liner

**Weight** 62 gsm  
**Colour** White, one side siliconised glassine  
**Thickness** 55 micron

**Application** Labels suitable for most substrates, including PE and PP.

**Shelf Life** 2 years

We reserve the right to supply comparable materials against any product without prior notice. The analysis, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms of Sale, and no recommendations for specific application or use are given. The user must satisfy as to the suitability of a particular grade for their own application.